

WATER DELIVERY HOSE

ID		OD	Working Pressure		Bursting Pressure		Bending Radius	Max. Coil Length
mm	Inch	mm	Bar	PSI	Bar	PSI	mm	Mtr.
31	1¼	41	10	150	30	450	190	40/LL
38	1½	48	10	150	30	450	230	40/LL
50	2	62	10	150	30	450	310	40/LL
63	2½	76	10	150	30	450	380	40
75	3	87	10	150	30	450	460	40
100	4	115	10	150	30	450	610	40
125	5	142	10	150	30	450	760	40
150	6	168	10	150	30	450	920	40
200	8	225	10	150	30	450	1220	40

TUBE:

Specially Compounded Synthtic Rubber, Black

REINFORCEMENT:

High Strength Synthetic Plies

COVER:

Black synthetic rubber cover

TEMP RANGE:

-40°C to +70°C

APPLICATIONS:

For all heavy duty air and water applications that require seamless conveyance in any industry

PROPERTIES:

Seamless
Uniform Thickness
Very Strong

APPLICABLE STANDARDS:

Indo-Maksson Propietory

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson Hydro Water Delivery Hose
I.D. W.P. India



Specification Subject to change due to Improvement in Quality [E&O.E].

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice. All products can be customized as per customer requirement in terms of working pressure and special ID & OD requests*

WATER HOSE LL*

ID		OD	Working Pressure		Bursting Pressure		Bending Radius		Weight	Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR	MTR
12.00	1/2	22.00	12	170	36	510	127	10.00	0.36	100
16.00	5/8	26.00	12	170	36	510	140	12.00	0.47	100
20.00	3/4	29.50	12	170	36	510	152	16.50	0.58	100
25.00	1	37.00	12	170	36	510	203	6.00	0.77	100
31.00	1.1/4	43.50	12	170	36	510	254	8.00	1.00	50
38.00	1.1/2	51.50	12	170	36	510	304	10.00	1.20	50
50.00	2	65.00	12	170	36	510	419	12.00	1.80	40

TUBE:

Specially Compounded Synthetic Rubber, Black

REINFORCEMENT:

Braiding of high strength synthetic fibre

COVER:

Black synthetic rubber cover

TEMP RANGE:

-40°C to +70°C

APPLICATIONS:

For all air and water applications that require seamless conveyance in any industry.

PROPERTIES:

Seamless
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

IS 444 - Type I & Type II

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Air/Water Hose I.D. W.P.
Made in India



*Long Length

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.