



THE VALUE CONNECTION IN

# INDUSTRIAL HOSE

## 500 MP/AIR DRILL HOSE

Yellow or Black Cover

Recommended For :

Heavy duty, high pressure use on Industrial, Construction & Pneumatic Mining applications, requiring an extra heavy duty hose with an oil resistant tube and highly abrasion resistant cover.

Suitable for usage in Air Compressor of high capacity.

TUBE : Specially compounded Nitrile Rubber. Black.

REINFORCEMENT : Single Braid of High Tensile Steel Wire.

COVER :

Option 1 : Specially Compounded Highly Abrasion Resistant Natural Rubber. Black.

Option 2 : Highly Abrasion Resistant Modified Nitrile Rubber. Yellow.

\*All sizes with perforated cover.

\*Yellow cover MSHA IC-11C, Flame Resistant.

Temperature Range : -30°C to +82°C



Available in Black & Yellow Cover

### SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm <sup>2</sup>	MPa	psi	Kg/cm <sup>2</sup>	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
20.0	3/4	28.3	1.11	34.5	3.45	500	138.0	13.8	2000	25.0	152.0	6.0	15.0	40.5
25.0	1	36.6	1.44	34.5	3.45	500	138.0	13.8	2000	25.0	200.6	7.9	15.0	40.5
31.5	1¼	44.2	1.74	34.5	3.45	500	138.0	13.8	2000	15.0	254.0	10.0	15.0	40.5
38.0	1½	50.5	1.99	34.5	3.45	500	138.0	13.8	2000	15.0	304.0	12.0	15.0	40.5
50.0	2	63.5	2.50	34.5	3.45	500	138.0	13.8	2000	15.0	355.0	14.0	15.0	40.5
63.5	2½	79.8	3.14	34.5	3.45	500	138.0	13.8	2000	10.0	762.0	30.0	15.0	40.5
76.2	3	93.2	3.67	34.5	3.45	500	138.0	13.8	2000	10.0	914.0	36.0	15.0	40.5

All hoses available as †Single length packaged in a single pack

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com

website : www.gatesind.com

Gates Connected