



THE VALUE CONNECTION IN

INDUSTRIAL HOSE

BLACKSNAKE GASOLINE HOSE

Exceed BS EN 1360 TYPE 3

Recommended For :

Dispensing all types of Petrol & Diesel fuels for Service Station Pumps.
A heavy duty hardwall hose which does not collapse in reel use or behind the nozzle in demanding service conditions.

TUBE : Specially compounded Nitrile Rubber. Black. Resistant to high Aromatic Gasoline.

REINFORCEMENT : Braided High Tensile Steel Wire.

COVER : Modified Nitrile Rubber. Black, Green, Blue, Yellow & Red.

Temperature Range : -30°C to +49°C



Available in Black, Green, Blue, Yellow & Red Cover

SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm ²	MPa	psi	Kg/cm ²	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
16.0	5/8	25.4	1.00	17.0	1.7	250	51.7	5.17	750	30.0	152.0	6.0	4.0 #	40.0 #
19.0	3/4	28.7	1.13	17.0	1.7	250	51.7	5.17	750	30.0	152.0	6.0	4.0 #	40.0 #
25.4	1	35.0	1.37	17.0	1.7	250	51.7	5.17	750	30.0	203.2	8.0	4.0 #	40.0 #

All hoses available as †Single length packaged in a single pack

*Available in multiples of 4m subject to max. length of 40m

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com

website : www.gatesind.com

