



THE VALUE CONNECTION IN

# INDUSTRIAL HOSE

## PETROL DISPENSING HOSE

Exceeds IS : 2396

Recommended For :

Dispensing all types of Petrol & Diesel fuels for Service Station Pumps.

Electrical conductivity : having two numbers braided copper flex wires laid spirally in opposite direction for electrical conductivity.

TUBE : Specially compounded Nitrile Rubber. Black. Resistant to high Aromatic Gasoline.

REINFORCEMENT : Two Braids of High Tenacity Synthetic Yarn.

Copper

wires ensure reliable conductivity.

COVER : Modified Nitrile Rubber. Black.

Temperature Range : -30°C to +49°C



### SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm <sup>2</sup>	MPa	psi	Kg/cm <sup>2</sup>	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
19.0	3/4	32.2	1.27	7.0	0.7	100	28.0	3.0	400	20.0	152.0	6.0	4.0#	40.0#
25.0	1	38.0	1.50	7.0	0.7	100	28.0	3.0	400	20.0	203.2	8.0	4.0#	40.0#

All hoses available as †Single length packaged in a single pack

\*Available in multiples of 4m subject to max. length of 40m

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com

website : www.gatesind.com

Gates Connected