



THE VALUE CONNECTION IN

INDUSTRIAL HOSE

ROCK DRILL HOSE

Exceeds IS : 446 Type 3

Recommended For :

Heavy duty, high pressure use on Industrial, Construction & Pneumatic Mining applications, requiring heavy duty hose with an oil resistant tube and abrasion resistant cover.

TUBE : Specially compounded Nitrile Rubber. Black.

REINFORCEMENT : Single Braid of High Tenacity Synthetic Yarn.

COVER :

- Specially Compounded Highly Abrasion Resistant Nitrile Rubber for Size 12.5 mm & 20.0 mm. Black.
- Highly Abrasion Resistant Modified Natural Rubber for Size 25.0 mm. Black.

Temperature Range : -30°C to +82°C



SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm ²	MPa	psi	Kg/cm ²	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
12.5	1/2	19.8	0.78	21.0	2.1	300	84.0	8.4	1200	25.0	127.0	5.0	15.0	—
20.0	3/4	28.0	1.10	21.0	2.1	300	84.0	8.4	1200	25.0	152.0	6.0	15.0	—
25.0	1	37.8	1.48	21.0	2.1	300	84.0	8.4	1200	25.0	203.0	8.0	15.0	40.5

All hoses available as †Single length packaged in a single pack

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com
website : www.gatesind.com

