



THE VALUE CONNECTION IN

INDUSTRIAL HOSE

SUPER SPRAY HOSE (AG SPRAY)

Exceeds IS : 1677 Type 4

Recommended For:

Very high pressure spraying of water based pesticides & chemicals in Agriculture & Forestry. Oil resistant tube ensures longer life.



TUBE: Modified Nitrile Rubber. Black

REINFORCEMENT : Single Braid of High Tenacity Synthetic Yarn.

COVER: Modified Nitrile Rubber. Black.

Temperature Range : -30°C to +82°C

SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm ²	MPa	psi	Kg/cm ²	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
10.0	3/8	21.0	0.83	55.0	5.5	800	165.0	16.5	2400	30.0	101.6	4.0	15.0	—
12.5	1/2	24.6	0.97	55.0	5.5	800	165.0	16.5	2400	30.0	127.0	5.0	15.0	—

All hoses available as †Single length packaged in a single pack

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com

website : www.gatesind.com

Gates Connected