



INDUSTRIAL RUBBER HOSES

OIL SUCTION & DISCHARGE HOSE

I.S. 10733 & I.S. 8129

DUNLOHiFLEX



-30°C / + 70°C
-22°F / +158°F

ID		OD	WP		BP		W
inch	mm	mm	bar	psi	bar	psi	g/m
1"	25.4	35	10	145	30	435	574
1 1/4"	32	42	10	145	30	435	716
1 1/2"	38	48	10	145	30	435	864
1 3/4"	44.5	55	10	145	30	435	1064
2"	50.8	62	10	145	30	435	1276
2 1/2"	63.5	75	10	145	30	435	1632
3"	76.2	88	10	145	30	435	1984
3 1/2"	90	104	10	145	30	435	2723
4"	101.6	116	10	145	30	435	3193
5"	127	143	10	145	30	435	4463
6"	152.4	168	10	145	30	435	5253

Application :

For suction discharge of gasoline, fuel and diesel oil from tanks and other transfer services

Construction :

- 1 G.I. Helix wire & 2 G.I. Helix wire.
- Cotton / synthetic fabric reinforcement.
- Oil resistance synthetic rubber tube.
- Oil, weather and abrasion resistance smooth outer rubber cover.
- Available in Smooth & Rough bore