



THE VALUE CONNECTION IN

INDUSTRIAL HOSE

SANDBLAST HOSE

Exceeds IS : 5894 Type 1

Recommended For :

Sand, Shot Blasting applications and where abrasive materials are carried at high velocity. Electrical conductivity : having two numbers braided copper flex wires laid spirally in opposite direction for electrical conductivity

(For coupling type please contact Gates Representative for further information)

TUBE : Specially Compounded Abrasion Resistant & Resilient Natural Rubber, Black.

REINFORCEMENT : High Tenacity Synthetic Yarn. Twin copper wires ensure reliable conductivity.

COVER : Specially Compounded Abrasion Resistant Natural Rubber, Black.

Temperature Range : -40°C to +70°C



SPECIFICATIONS

NOMINAL I.D.		MEAN O.D.		WORKING PRESSURE			MIN. BURST PRESSURE			VACUUM	BEND RADIUS		PACKING SPECS.† LENGTH IN METRES	
mm	inch	mm	inch	Kg/cm ²	MPa	psi	Kg/cm ²	MPa	psi	in. Hg	mm	inch	Min.(Lgth)	Max.(Lgth)
20.0	3/4	38.6	1.52	7.0	0.7	100	35.0	3.5	500	15.0	203.2	8.0	15.0	40.5
25.0	1	45.1	1.78	7.0	0.7	100	35.0	3.5	500	5.0	304.0	12.0	15.0	40.5
31.5	1¼	52.7	2.07	7.0	0.7	100	35.0	3.5	500	5.0	304.0	12.0	15.0	40.5
38.0	1½	58.5	2.30	7.0	0.7	100	35.0	3.5	500	5.0	457.2	18.0	15.0	40.5
50.0	2	71.8	2.83	7.0	0.7	100	35.0	3.5	500	5.0	508.0	20.0	15.0	40.5

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com

website : www.gatesind.com





THE VALUE CONNECTION IN

INDUSTRIAL HOSE

SAND BLAST WRESTLER HOSE

WRESTLER SAND BLAST HOSE

- Recommended For:** Highly abrasive material used in Sand Blasting applications including River Sand Garnets, Copper Slag, Coal Particles, Corundum, Cast Steel, Grit Glass etc. Specially designed for superior performance-longer life due to very low tube wear.
- Tube:** Excellent abrasion resistant, Anti-static, Modified natural rubber [Black]
- Reinforcement:** Single high-tenacity synthetic yarn for (3/4" & 1" sizes). Double yarn braid for 1-1/4" & 1-1/2" sizes.
- Cover:** Specially compounded abrasion resistant & resilient natural rubber [Black].
- Temp. Range:** -40°C to +75°C
- Standard:** Meets IS: 5894



1 1/4"-1 1/2" 3/4"-1"

SPECIFICATIONS

PRODUCT DESCRIPTION	PRODUCT NO.	Ø		Ø	P		P		L		Ø	METER ROLL
		(in)	(mm)		(mm)	(psi)	(Bar)	(psi)	(Bar)	(mm)		
12 SAND BLAST HOSE - WRESTLER	41290817	3/4"	19.1	33.2	175	12.0	700	48.0	178	7.0	25	-
16 SAND BLAST HOSE - WRESTLER	41290818	1"	25.4	39.2	175	12.0	700	48.0	229	9.0	25	-
20 SAND BLAST HOSE - WRESTLER	41290819	1 1/4"	31.8	48.2	175	12.0	700	48.0	254	10.0	25	-
24 SAND BLAST HOSE - WRESTLER	41290820	1 1/2"	38.1	56.2	175	12.0	700	48.0	304	12.0	20	-

The World's Most Trusted Name in Hose and Connectors



A Tomkins Company

Gates India Pvt. Ltd.

Ambala-Chandigarh Highway, Lalru - 140 501 (Punjab)

Tel : 01762-274050-53 Fax : 01762-274151-52 E-mail : customercare@gatesind.com
website : www.gatesind.com

